

- **Endless retailing possibilities, provided by optimum product presentation and vend mechanism flexibility**
- **Technology proven in US and European vending markets**
- **Manufactured in India, for India**
Installed at Metro, Airport & Corporate office locations
- **Designed for reliability, simple maintenance and service.**



Innovative LED Lighting

*Increasing sales by up to 12%
Minimising power consumption
Reducing service calls with a
lifetime of over 50,000 Hrs*

**Unique
Vend Sensor**



- **Hard-wearing all steel design, for low life-time costs**
- **Easily serviced refrigeration deck, accessed from the front**
- **Dual Coils as Standard, for optimum product presentation and vend performance**
- **Instant display of Audit Totals**

PHYSICAL CHARACTERISTICS

Finish: Powder Coat paint

Number of Trays: 5 Standard (SEC3520, 3530, 3540), 6 Standard (3510)

ENVIRONMENT

Location Environment: Indoors only

(Defined as <30°C ambient temperature and <65% Relative Humidity)

ELECTRICAL REQUIREMENT

Requires one (1) 220 VAC 12 Amps grounded outlet


Specifications

*Indoor installation only.
Specification subject to change without notice.*


	SEC3510 Ambient	SEC3520 Refrigerated	SEC3530 Refrigerated (Dual-Zone)	SEC3540 Refrigerated
Height	183 cm	183 cm	183 cm	183 cm
Width	89 cm	89 cm	89 cm	89 cm
Depth	93 cm	93 cm	93 cm	93 cm
Floor Space	0.812 SqMt	0.812 SqMt	0.812 SqMt	0.812 SqMt
Packing Size	1.59 CuMt	1.59 CuMt	1.59 CuMt	1.59 CuMt
Voltage (AC)	220V AC	220V AC	220V AC	220V AC
Hertz	50Hz	50Hz	50Hz	50Hz
Running Amperes	1Amp.	5Amp.	5Amp.	5Amp.
Watts	300 Watts	750 Watts	750 Watts	750 Watts
Refrigerant Type	-	134a	134a	134a
Refrigerant Charge	-	350 Grms.	350 Grms.	350 Grms.
Shipping Weight	213 kg	298 kg	319 kg	317 kg

Models and Capacity


SEC3510



SEC3520



SEC3530



SEC3540

